



AreaRAE

Rapid Deployment Kit System Package for Hazardous Environment Detection

The AreaRAE is a one- to five-sensor gas detector equipped with a wireless RF (radio frequency) modem which allows the unit to communicate and transmit readings and other information on a real-time basis with a remotely located base controller.

The AreaRAE is a rugged, weather-resistant, portable monitor that can run over 18 hours on rechargeable Lithium-ion batteries. It is also the first "lunchbox"-type multi-sensor instrument able to include a photoionization detector (PID) for parts-per-million measurement of volatile organic compounds (VOCs), as well as LEL, O₂ and up to two electrochemical toxic sensors to measure specific toxic substances such as CO and H₂S.

The RF modem allows real-time data transmissions with a base controller located up to two miles away from the AreaRAE detector. A personal computer can be used as the base station for an AreaRAE system. The standard ProRAE Remote software used to control AreaRAE systems is capable of monitoring the input of up to 64 remotely located monitors.

AreaRAE options include the ability to track and display readings from remotely located detectors on a GPS map.

The AreaRAE is ideal for HazMat and other emergency response monitoring programs. AreaRAE detectors can be used to quickly establish an emergency perimeter by setting out multiple monitors at strategic locations, then backing off to a position of safety to monitor readings over the wireless link.

The AreaRAE is available individually or as part of the Rapid Deployment Kit (RDK) system package.

Key Features

- Up to five sensors (PID, LEL, O₂ and two toxic)
- Loud buzzer and large, extra-bright warning light
- Large LCD display and keypad
- Rugged, weather-resistant housing
- Built-in pump
- Interchangeable Lithium-ion or alkaline battery pack
- Continuous operation via AC source

Additional Advantages

- Real-time wireless data transmission with built-in RF modem
- View real-time sensor data and alarm status at headquarters or command center
- ProRAE Remote software simultaneously controls and displays readings for up to 64 remote detectors
- License-free, ISM-band RF transmission with communication range up to 2 miles (extendable with RAELink Repeaters)
- Optional wall-mounting bracket or field mounting tripod adapter
- Optional GPS provides ability to track and display readings from remote detectors

Applications

- HazMat and Emergency Response
- Refineries and Petrochemical Plants
- Confined Space Entry
- Power Plants
- Pulp and Paper Industry
- Plant and Mill Turnarounds
- Marine and Offshore Wells



 **Wireless**

 **GPS**

www.raesystems.com

ISO 9001
CERTIFIED

CE

SP
US

 **RAE**
SYSTEMS

Specifications*

Detector Specifications

Size	9.25" L x 5.0" W x 9.25" D (235mm L x 127mm W x 235mm D) without handle
Weight	8.5 lbs. (3.9 kg) with battery pack
Sensors	Up to five sensors (O ₂ , combustible, two toxic and VOC), electrochemical sensors for toxic gases and oxygen, photoionization sensor for VOC, catalytic combustion sensor for combustible gases
Battery	Rechargeable, 7.4V/4.5Ah, Lithium-ion battery pack with built in charger (less than 10 hours charge time) or a 6 C-size alkaline battery pack
Operating Hours	Up to 18 hours continuous operation
Display	2-line, 16-digit LCD with manually activated LED back light
Keypads	3 operation and 4 programming keys
Direct Readout	Instantaneous values, sensor name, high and low values for all detectors, TWA and STEL values for toxic gases and VOCs, battery voltage and elapsed time
Alarm	Flashing red LED cluster to indicate exceeded preset limits, low battery or sensor failure
Alarm Setting	Separate alarm limit settings for TWA, STEL, Low and High alarm
Audible Alarm	110dB buzzer at 10cm (typical)
Visual Alarm	Flashing red LED cluster
Alarm Mode	Latching/automatic reset
Datalogging	4,000 points for each sensor with time stamp, serial number, user ID, site ID
Data Storage	20,000 readings (64 hours, 5 channels at 1-minute intervals) in non-volatile memory
Datalog Interval	Programmable 1 to 3600 sec
Communication	Upload data to PC and Download monitor setup from PC through RS-232 link to serial port on PC
EM Immunity	No effect when exposed to 0.43 mW/cm ² RF interference (5-watt transmitter at 12 inches)
Safety Certification	CSA Classified for use in Class I, Division 2, Groups A,B, C, and D (w/ 900 MHz modem)
Frequency	902 to 928 MHz (License-free)
RF Range	Up to 2 miles (900 MHz) - extendable with RAELink2 Repeaters
Calibration	Two-point field calibration for fresh air and standard reference gas
Sampling Pump	Internal integrated diaphragm pump with programmable High (400cc/min) and Low (300cc/min) flow rate settings
Low Flow Alarm	Auto shut off pump at low flow condition
Temperature	-4° to 113°F (-20° to 45°C)
Humidity	0% to 95% relative humidity (non-condensing)
Optional	Integrated GPS receiver

*Specifications are subject to change

DISTRIBUTED BY:

RAE Systems Inc.	USA/Canada	1-877-723-2878
3775 North First Street	Europe/Russia	+45 8652 5155
San Jose, CA 95134 USA	Middle East/Australia	971 50 429 1385
raesales@raesystems.com	China	8610 58858788
	Asia	+852 2669 0828

www.raesystems.com

DS-1004-04

Sensor Specifications

Gas Monitor	Range	Resolution
Oxygen	0 to 30.0%	0.1%
Combustible	1 to 100% LEL	1% LEL
VOCs	0 to 199 ppm 200 to 2,000 ppm	0.1 ppm 1 ppm
Carbon Monoxide	0 to 500 ppm	1 ppm
Carbon Monoxide	10 to 2000 ppm	10ppm
Hydrogen Sulfide	0 to 100 ppm	1 ppm
Sulfur Dioxide	0 to 20.0 ppm	0.1 ppm
Nitric Oxide	0 to 250 ppm	1 ppm
Nitrogen Dioxide	0 to 20.0 ppm	0.1 ppm
Chlorine	0 to 10.0 ppm	0.1 ppm
Hydrogen Cyanide	0 to 100 ppm	1 ppm
Ammonia	0 to 50 ppm	1 ppm
Phosphine	0 to 5.0 ppm	0.1 ppm
Hydrogen Chloride	2 to 15 ppm	1 ppm
Hydrogen Fluoride	2 to 10 ppm	1 ppm

Monitor only includes:

- Monitor as specified
- Sensors as specified
- Carbon filters (for units with CO sensor)
- Calibration adapter
- Quick reference guide
- Operation and maintenance manual
- Shoulder strap
- Rechargeable Lithium-ion battery pack
- 120/240 VAC AC/DC Adapter
- Spare alkaline battery pack
- 10 spare external filters
- Hard transport case with pre-cut foam
- 15' (5m) Teflon[®] tubing
- Tool kit

Instrument with calibration kit also includes:

- Calibration gas (kit may contain multiple cylinders, depending on the sensors installed)
- Calibration regulator and tubing (kit may contain a second regulator, depending on the types of calibration gases included)
- Hard transport case with pre-cut foam interior padding

Datalogging Monitors also include:

- Software, ProRAE Suite Package for Windows 98, NT, 2000 and XP
- Computer interface cable

ProRAE Remote Basic Host Software Package includes:

- ProRAE Remote Software for Windows[®] 98, NT, 2000 and XP
- RAELink Modem

AreaRAE Model Numbers:

- AreaRAE with RF modem: PGM-5020
- AreaRAE with RF modem & GPS option: PGM-5020

