

MicroRAE

Wireless 4-Gas Monitor

The MicroRAE four-gas portable detector brings enhanced user-friendliness and flexibility to wireless gas detection. This enables continuous, instant visibility of safety threats for faster, more informed decisions, to protect workers, facilities, and the environment, and to optimize operations.

The MicroRAE is a wireless diffusion detector that simultaneously monitors up to four gases, including hydrogen sulfide, carbon monoxide, oxygen and combustibles (LEL). With its different wireless connectivity options the MicroRAE can deliver real-time instrument readings and alarm status to other wireless offerings such as ConneXt Plus, ConneXt Pro, ConneXt Loneworker⁴ and Safety Communicator.

- Man Down Alarm with real-time remote wireless notification¹
- GPS module for location
- Bluetooth® low energy connection to a Smart Phone device for uplink data communication and device configuration
- Remote notification and Panic function
- Fully automated bump testing and calibration with AutoRAE 2



Industries

Personal protection and general safety and compliance in:

- Lone Worker Applications
- Oil and Gas
- Waste water treatment
- Utilities
- Telecommunications
- Firefighting
- Petrochemicals
- Construction



Optional Accessories

- AutoRAE 2 Automatic Test and Calibration Systems
- Gang Charger (5 units)
- Auxiliary filter
- Hand pump kit
- Truck mount charger

FEATURES & BENEFITS

- Honeywell ConneXt compatible with Mesh and Wifi wireless configurations
- Compact and lightweight
- IP-67 water- and dust-resistant case
- Strong, protective, concussion-proof design
- Real-time gas concentration readings, location, alarm and status enabled by state of-the-art wireless technology
- Unmistakable five-way local and remote notification of alarm conditions
- Short bump test and calibration time
- Global approval for worldwide acceptance
- Filtered LEL sensor options to inhibit sensor poisoning
- Compatible with Safety Communicator
- Device Management with Honeywell SafetySuite

MicroRAE Specifications

INSTRUMENT SPECIFICATIONS		
SIZE	4.6 x 3.0 (2.6) 3.0 x 0.9 in (117 x 76 (66) 74 x 24mm)	
WEIGHT	7.03 oz (206g) (including Li-ion battery and clip)	
SENSORS	LEL Catalytic bead for combustibles, Liquid Oxygen (O ₂), Electrochemical Sensor for CO, H ₂ S, HCN	
BATTERY	Rechargeable Li-ion	
RUNNING TIME	15 hours continuous non-wireless, 11 hours continuous wireless Note: All battery specifications at 68° F (20° C); lower temperatures and alarm conditions will affect runtime	
DISPLAY GRAPHIC	Monochrome display, 1.73 x 1.29 in (44 x 33 mm) with 2 color back light modes	
KEYPAD	Two-button operation	
DIRECT READOUT	Real time reading of gas concentration and Man Down indicators Multiple units display options Wireless and GPS ON/OFF and reception quality STEL, TWA, peak, and minimum values Intelliflash and policy enforcement indicators	
ALARMS	Multi-tone 100dB buzzer (at 11.8"/ 30 cm, typical), vibration alarm, and flashing LEDs and on-screen indication of alarm conditions Alarms: latching, non latching or manual override Additional diagnostic alarm and display message for low battery Wireless connectivity alarm Man Down Alarm and real-time remote wireless notification	
DATALOGGING	Continuous datalogging (6 month for 4 sensors at 1-minute intervals) User-configurable datalogging intervals (from 1 to 3,600 seconds)	
COMMUNICATION & DATA DOWNLOAD	Data download and instrument set-up and upgrades on PC via Travel Charger Wireless data and status transmission via built-in RF modem (optional)	
WIRELESS NETWORK	RAE Dedicated Wireless Mesh network or Standard WiFi	
WIRELESS RANGE (TYPICAL)	Up to 650 ft (200m) for sub1GHz Mesh Radio ³ , Up to 330 ft (100m) for WiFi ³ , Up to 15 ft (5m) for BLE	
EMC/RFI	EMC directive: 2004/108/EC	
IP RATING	IP-67	
CALIBRATION	Two-point calibration (manual, or automatic with AutoRAE 2) US & Canada: Class I, Division 1, Groups A, B, C and D	
SAFETY CERTIFICATIONS	 II 2G Ex ia d IIC T4 Gb  I M1 EX ia I Ma	
TEMPERATURE	-4° to 140° F (-20° to 60° C) for T4 temperature code	
HUMIDITY	0% to 95% relative humidity (non-condensing)	
ATTACHMENTS	Stainless-steel alligator clip; wrist wrap (optional)	
WARRANTY	2-year warranty on device and sensors ²	
MODEL NUMBER	PGM26XX	
WIRELESS	ISM license free band. IEEE 802.15.4 Sub 1 GHz, IEEE 802.11 bands b/n/g 2.4 GHz	
WIRELESS APPROVALS	FCC Part15, CE R&TTE, Bluetooth 4.0, GPS, Others ⁴	
GAS MONITOR	RANGE	RESOLUTION
OXYGEN (O ₂)	0 to 30.0%	0.1%
COMBUSTIBLE	0 to 100% LEL	1% LEL
CARBON MONOXIDE (CO)	0 to 1,000 ppm	0 – 250 ppm / 1 ppm
		250 – 1,000 ppm / 3 ppm
HYDROGEN SULFIDE (H ₂ S)	0 to 100 ppm	0 – 50 ppm / 0.1 ppm
		50 – 100 ppm / 1 ppm
HYDROGEN CYANIDE (HCN)	0 to 50 ppm	0.2 ppm

- 1 Additional equipment and/or software licenses may be required to enable remote wireless monitoring and alarm transmission
- 2 Against factory defects
- 3 Receiving > 80%
- 4 Contact RAE Systems for country specific wireless approvals and certificates

Specifications are subject to change

ORDERING INFORMATION

- Refer to the Portables Pricing guide for monitor configurations and accessories

DOWNLOAD YOUR FREE TRAINING APP



For more information
www.honeywellanalytics.com
www.raesystems.com

Europe, Middle East, Africa
 Life Safety Distribution GmbH
 Tel: 00800 333 222 44 (Freephone number)
 Tel: +41 44 943 4380 (Alternative number)
 Middle East Tel: +971 4 450 5800 (Fixed Gas Detection)
gasdetection@honeywell.com

Americas
 Honeywell Analytics Distribution Inc.
 Tel: +1 847 955 8200
 Toll free: +1 800 538 0363
detectgas@honeywell.com
 Honeywell RAE Systems
 Phone: +1 408 952 8200
 Toll Free: +1 888 723 4800

Asia Pacific
 Honeywell Analytics Asia Pacific
 Tel: +82 (0) 2 6909 0300
 India Tel: +91 124 4752700
 China Tel: +86 10 5885 8788-3000
analytics.ap@honeywell.com

Technical Services
 EMEA: HAexpert@honeywell.com
 US: ha.us.service@honeywell.com
 AP: ha.ap.service@honeywell.com

Datasheet_MicroRAE_DS-1121-07_US-EN
 07/18 ©2018 Honeywell International Inc.

Device Management with Honeywell SafetySuite



honeywellanalytics.com/SafetySuite

